



Futuremed America Inc.
15700 Devonshire St., Granada Hills, CA 91344-7225 USA
Phone 1-818-830-2500 Fax 1-818-891-4755

Toll Free: 1-800-222-6780

info@futuremedamerica.com www.futuremedamerica.com

Easy ECG plus

- Minimum hardware requirement
- Easily installed on a standard Windows notebook or desktop
- Economical and cost-effective
- Full page reports on standard copy paper
- Zoom Function
- Two or more reports can be displayed and compared simultaneously
- In addition to standard demographic information, patient records can include physician's notes and comments
- Unlimited number of patient files can be stored internally and on removable media
- Study each waveform recorded during acquisition and adjust morphology with related measures of time and amplitude
- Compatible with Windows network protocols
- Individual tests, or complete patient files, can be transmitted to other stations or stored electronically

| THE REAL PROPERTY. | AD N | CHICK THE R. | Section 18. | All residents | AND 1 |
|-------------------------|-------------------|--------------|-------------|---------------|-------|
| | harlant | IL | -1- | - | -1 |
| and a section and as as | more | | | | -1 |
| - landandan | Janka | | | | |
| | | 1 | | | |
| 1 1 1 | 1 1 | | | hand | - |
| | | 00 H | 1 | - | ala 1 |
| | 1 | and labor | | make | mon ! |
| -dadada | And | | 1 | | 1 1 |
| mhhhh | July | | 1 | | |
| -1-4-4- | 4-4- | X L | -la | سلسا | -la |
| - dan dan dan | - James | 40 hay | | | -4- |
| | diameter. | 40- | | - | -b |
| | and an extendible | | 1 | | |



Hardware Characteristics

- Isolated preamplifier in accordance with IEC 601-1
- Input impedance > 50 Mega Ohms
- Defibrillator protected
- Simultaneous 12 leads ECG acquisition at 512 sample/second
- A/D converter at 12 bit (3.5uV LSB)
- C.M.R.R. > 100dB
- Patient cable with 10 leads
- 9V battery power supply
- CE0470 mark in accordance with 93/42 EEC



Minimum System Requirements

- Pentium II or better
- 64 MByte RAM
- SVGA display card w/ 64 Meg VideoRam
- Mouse or other pointing system
- Serial input RS232C
- Microsoft WIN'98 or NT/2000/XP
- Microsoft Direct X 5.0 or higher

Software Characteristics

- Functions available by keyboard or mouse
- Sampling rate: 512 Hz
- Selectable sensitivity (.1/.2/.5/1/2 mm/mV)
- Filters: L.P. 30, 70, 150, 250 Hz; Time constant 1.6, 3.2 sec; Notch 50, 60 Hz
- Ability to monitor from 1 to 12 leads in real time
- Automatic measurement on 12 leads
- Trending of heart rate from 30 minutes to 24 hours, with alarm
- ECG averages
- Optional Interpretation
- Multiple Window management with the ability to compare traces both in acquisition and review
- File storage in PARADOX format, with patient data and trace management (optional ORACLE or SQL format)
- Ability to search database using patient name or ID
- Ability to modify or change acquisition parameters
- Zoom function with measurement capability
- Ability to print resting ECG reports in various formats (including 12 lead) using Windows compatible printers
- Ability to archive tracings on hard disk or removable media

<u>FUTUREMED</u>

Phone: 1-800-222-6780 or 1-818-830-2500 • Fax: 1-818-891-4755 e-mail:info@futuremedamerica.com • www.futuremedamerica.com Futuremed America Inc., 15700 Devonshire St., Granada Hills, CA 91344 USA